

PERMA-CRIL

Acrylic Sealer

DESCRIPTION

Perma-Cril is an acrylic sealer for the preparation of walls with traces of paints, lime, moisture and salty areas etc. prior to painting with *Perma-Paint*.

FEATURES

Perma-Cril is ideal for the treatment of wall surfaces with existing paint. It is a sealer primer on weak wall surfaces with different water absorption. It protects the walls and acts as a waterproof barrier and bonding agent to give *Perma-Paint* a strong and evenly finish.

Perma-Cril is an easy-to-apply acrylic sealer and once dry forms a protective sheet without joints and an impermeable barrier.

APPLICATION

Perma-Cril is ready to use. Stir the container well. The surface to be sealed must be consistent, clean, dry and free of dust. Use a paint roller or a paint brush.

Apply one or two coats according to the surface condition.

Perma-Cril can also be applied on new unpainted surfaces.

TECHNICAL DATA

Nature	Acrylic Monomers
Colour	Clear
Density	1.1-1.2 Kg / liter
Coverage	16-20 m ² / kg
Drying at 23° C 60% RH	1-2 hours
Application methods	Brush or roller

PACKAGING

Plastic bucket of 10 kgs.

Once the bucket is opened, use the product within one month. Always keep unused quantity in a tightly sealed container.

One year shelf life.

Note

Instructions of use are given based on our testing and knowledge and do not imply any commitment. Said instructions do not free the user from examining and verifying the product for its correct use. Manufacturer's liability is limited to the value of the used goods. Complaints must be accompanied with the original package to allow proper traceability.