

PERMA-FILLER

Putty Filler

DESCRIPTION

Perma-Filler is an essential putty product for creating smooth surfaces for painting and decorating walls and ceilings.

FEATURES

Perma-Filler is a copolymer based putty filler, ideal for smoothing walls, filling unsightly cracks and hiding any imperfections on the wall.

Easy application. Provides an excellent base for subsequent coats and it is free from harmful chemicals like APEO, formaldehyde, heavy Metals etc.

APPLICATION

Ideal for interior surfaces.

The surface must be absorbent, dry and free of dust. On smooth / non-absorbent cement surfaces, a suitable primer (PermaFlex) must be applied.

When applying Perma-Filler use a spatula and remove any excess material.

Apply maximum 1 mm material to avoid roughness up to 3 coats of the product, if necessary.

Before applying a second coat, the front must be completely dry. It is important to let the paste dry well between each hand, to avoid cracks due to material retraction.

Once dry, use sandpaper to smooth the surface smoothly. The maximum thickness of the paste must be 3 mm.

TECHNICAL DATA

<u>Colour</u>	<u>White</u>
<u>Consistency</u>	<u>Soft and Pasty</u>
<u>Working Time</u>	<u>4 minutes</u>
<u>Drying Time</u>	<u>Approx. 1hour 30 min</u>
<u>Density</u>	<u>1.3 - 1.45 kg</u>
<u>Performance</u>	<u>400 grams / m² - one coat</u>

PACKAGING

Plastic bucket of 7kgs.

One year shelf life. Once the bucket is opened, the time to use the product is approx.1 month, if it has been sealed tightly.

Note Instructions of use are given based on our testing and knowledge and do not imply any commitment. Said instructions do not free the user from examining and verifying the product for its correct use. Manufacturer's liability is limited to the value of the used goods. Complaints must be accompanied with the original package to allow proper traceability.