

# PERMA-LASTIC *Primer*

## PAINT PRIMER

### **DESCRIPTION**

*Perma-Lastic Primer* is a ready to use base coating primer applied on walls prior to the application of *Perma-Paint*, with elastic and waterproof characteristics, without tars or bituminous products.

### **FEATURES**

*Perma-Lastic Primer* acts as a damp proof barrier between the wall and the paint. It has good bonding properties and seals the fine cracks prior to painting with *Perma-Paint*. It is an easy-to-apply primer and forms a protective sheet without joints and an impermeable elastic barrier.

### **APPLICATION**

Stir the container well. The surface to be painted must be consistent, clean, dry and free of dust.

Use a paint roller or a paint brush.

It is enough to apply one coat.

### **TECHNICAL DATA**

Nature	Modified acrylic
Finish	Semi-Mate
Colour	White
Density	1.0-1.3 Kg / liter
Coverage	7 m <sup>2</sup> / kg
Drying at 23° C 60% RH	6-8 hours
Application methods	Brush, roller and gun
Dilution	Water

### **PACKAGING**

Plastic bucket of 10 kgs.

Once the bucket is opened, use the product within one month.

Always keep unused quantity in a tightly sealed container.

One year shelf life.

#### **Note**

Instructions of use are given based on our testing and knowledge and do not imply any commitment. Said instructions do not free the user from examining and verifying the product for its correct use. Manufacturer's liability is limited to the value of the used goods. Complaints must be accompanied with the original package to allow proper traceability.