

PERMA-PAINT

ACRYLIC PAINT

DESCRIPTION

Perma-Paint is a matt paint based on acrylic-vinyl polymerization resins in aqueous dispersion, it is resistant to wet rubbing, good opacity, impermeable to rain and vapors. Good resistance to erosion and wear in very aggressive environments.

FEATURES

Perma-Paint is ideal for interior and exterior walls and ceilings, easy to apply, for the protection of facades, commercial premises, interiors and exterior of houses on surfaces of plaster, cement etc.

APPLICATION

GENERAL RECOMMENDATIONS: Stir the container well. The surfaces to be painted must be clean, dry and consistent.

SURFACES NOT PREPARED: On surfaces in good condition, apply a first coat diluted with 10-15% of water. Then apply a second layer undiluted. On surfaces in poor condition: Clean all affected areas, removing all loose material and clean all the dirt and dust they may have accumulated. To consolidate the substrate and homogenize porosity it is advisable to apply a first coat of *Perma-Lastic Primer*.

MAINTENANCE OF PREVIOUSLY PAINTED SURFACES IN GOOD CONDITION: Directly apply the previously washed or brushed surface by diluting the first layer with 10-15% water, then apply the second layer as is.

MAINTENANCE OF PREVIOUSLY PAINTED SURFACES IN POOR CONDITION: Completely remove old paint and proceed as on new surfaces.

TECHNICAL DATA

Nature	Vinyl
Finish	Matt
Color	ALL
Density	1.30-1.45 Kg / liter
Performance	6.5-8 m ² / Kg
Drying at 23° C 60% RH	30-60 minutes
Repainted at 23°C 60% RH	8 hours
Application methods	Brush, roller and gun
Dilution	Water
Fire resistance	M-1
Application conditions HR≤80%	+ 10°C + 35°C
Volume in solids	40-45%

PACKAGING

Plastic bucket of 5 or 23 kgs.
Always keep unused quantity in a tightly sealed container.
One year shelf life.

Note

Instructions of use are given based on our testing and knowledge and do not imply any commitment. Said instructions do not free the user from examining and verifying the product for its correct use. Manufacturer's liability is limited to the value of the used goods. Complaints must be accompanied with the original package to allow proper traceability.